



Advancing the Power of the Sun

Bifacial Module 365-385W

BVM6612M- (SERIES) BF

0~+5W


Power Tolerance

19.5%

Maximum Efficiency

365-385W

Power Output Range



78.39x39.06 Inches

Silver Frame / Transparent Backsheet



High Quality and Reliable Modules

- ◆ Transparent backplane technology, more power generation
- ◆ Withstand up to 5400 Pa snow load and 2400 Pa wind load
- ◆ 2 EL inspections per cell/module for defect-free consistency
- ◆ Type 1 fire-rating per UL 1703 edition 3
- ◆ High salt and ammonia resistance certified by TUV Rheinland
- ◆ 0~+5 W guaranteed positive tolerance
- ◆ Rugged design for long-term durability; passed extended reliability tests



Warranty

- ◆ 12-year product warranty
- ◆ 25-year linear power output warranty



Comprehensive Certificates for Products and Management

- ◆ UL 1703, IEC 61215, IEC 61730, CEC listed, MCS and CE
- ◆ ISO 9001 for Quality Management Systems
- ◆ ISO 14001 for Environmental Management Systems
- ◆ OHSAS 18001 Occupational Health and Safety Systems

Listed in Bloomberg New Energy Finance's tier 1 list as of 1Q 2018



2107 N 1st Street Suite 550 San Jose, CA 95131

BOVIETSOLARUSA.COM ♦ 877.253.2858 ♦ SALES@BOVIETSOLARUSA.COM

Electrical Characteristics STC					
	BVM6612M-365-BF	BVM6612M-370-BF	BVM6612M-375-BF	BVM6612M-380-BF	BVM6612M-385-BF
Maximum Power (Pmax)	365W	370W	375W	380W	385W
Maximum Power Current (Imp)	9.40A	9.50A	9.58A	9.66A	9.74A
Maximum Power Voltage (Vmp)	38.90V	39.02V	39.22V	39.41V	39.60V
Short Circuit Current (Isc)	9.79A	9.89A	9.96A	10.04A	10.11A
Open Circuit Voltage (Voc)	47.6V	47.7V	48.00V	48.30V	48.50V
Module Efficiency	18.5%	18.7%	19.0%	19.2%	19.5%
Power Tolerance	0~+5W	0~+5W	0~+5W	0~+5W	0~+5W
STC: AM1.5, Irradiance 1000W/m ² , 25°C					

Electrical Characteristics NOCT					
	BVM6612M-365-BF	BVM6612M-370-BF	BVM6612M-375-BF	BVM6612M-380-BF	BVM6612M-385-BF
Maximum Power (Pmax)	269W	273W	277W	281W	284W
Maximum Power Current (Imp)	7.50A	7.57A	7.64A	7.71A	7.77A
Maximum Power Voltage (Vmp)	35.9V	36.1V	36.3V	36.5V	36.6V
Short Circuit Current (Isc)	7.98A	8.05A	8.12A	8.19A	8.26A
Open Circuit Voltage (Voc)	44.0V	44.3V	44.6V	44.9V	45.2V
NOCT: AM1.5, Irradiance 800W/m ² , 20°C, Wind speed 1m/s					

Mechanical Characteristics		Thermal Characteristics	
Solar Cell	Bifacial- Monocrystalline 6.14 x 6.14 inch, 72 (6 x 12) pcs. in series	Pmax Temperature Coefficient	-0.38%/K
Glass	High transparency, low iron, AR coated tempered glass 3.2 mm (0.13 inch)	Voc Temperature Coefficient	-0.30%/K
Frame	Anodized aluminum alloy	Isc Temperature Coefficient	+0.06%/K
Junction Box	Ip67 rated, with 3 bypass diode	NOCT	113±3.6°F
Output Cable	4 mm ² (EU)/12 AWG (US), on request		
Connector	MC4 compatible		
Dimension	78.39x39.06 x 1.38 Inches		
Weight	51.81lb		

Maximum Ratings		Packing Information	
Operating Temperature	-40°F~185°F	Pieces per pallet	30
Maximum Series Fuse Rating	20A	Pallets per container (40HQ)	24
Maximum System Voltage	1000/1500V DC	Pieces per container (40HQ)	720
		Pallet weight/size	1650.4 lb/79.72 x 43.31 x 45.88 inch

